

PRODUCT
BROCHURE



Origin
aluminium

DOORS | WINDOWS | SHOWERS

ORIGUARD | COMMERCIAL



www.origingroup.co.za

Tested and Certified Products

Origin Aluminium, founded in 2005, is a national producer of Aluminium and Glass architectural products. It was the brainchild of Grant Kalil (CEO) who, together with Grant Saville (Western Cape and Group COO), Kevin Minnaar (Gauteng), Rajen Naicker (KwaZulu Natal), Kisten Naicker (Free State), Charles Honeywill (Eastern Cape) and Brett Kalil (Group FD) have between them over 175 years of experience in the industry.

This energized and experienced team was given an enormous boost with Neville Kalil taking up the role of chairman of the group. Neville was a co-founder of Kal Aluminium and brought to Origin a wealth of experience and respect from the industry. His technical and management skills, combined with the dynamic approach of the younger members of the team, have all contributed to the success of Origin as a reliable supplier of quality, ready-to-install, finished products at competitive prices.

With manufacturing facilities in Gauteng, the Western & Eastern Cape, KwaZulu Natal and the Free State, Origin's objective is to become the vehicle via which its clientele can prosper by confidently concentrating their efforts on negotiating and winning contracts instead of concerning themselves with the problematic issues surrounding manufacturing. Through improved efficiencies, innovative design and motivated support teams, Origin believes it is able to make their products quicker than and at least as well as any other manufacturer.

Sales, financial, manufacturing and support staff have all been handpicked in all regions and consist of highly motivated and energized individuals, experienced in the industry and fully committed to the success of their various portfolios within the company. Many staff members enjoy equity in the company, further incentivising their efforts.

Origin is an AAAMSA member and continuously tests its products to the strict requirements of the new building regulations regarding deflection, glazing, water and air infiltration. Origin's domestic patio door became the first in the country to adhere to the SANS 10400 and 10137 wind deflection tests, whilst our Casement window has been successfully tested to the AAAMSA A3 rating. In 2009, further successful tests were achieved on the Vertical Slider (A1), the Horizontal Slider (A2), the Side Hung window (A1), the Curtain Wall (A4) and the Shopfront (A3). Our products have been designed with these specifications in mind as well as factors such as aesthetics, handling, installation and cost. R and D work is always ongoing on current and upcoming regulations and products.

During 2013, Origin Aluminium achieved the much sought after SAFIERA Energy Rating Certifications for the Origin Patio Door and the Origin 340 Casement Window. This certification provides home owners, architects & builders all the necessary energy and mechanical performance information required when building a new home and planning for optimal energy efficiency. Both certificates together with all the ratings & results are available for download on our website www.origingroup.co.za

Sound relationships with top suppliers and market leaders, put Origin Aluminium in a position to fully service its market in all aspects and as one of the very few independent manufacturers in the Aluminium Industry, it has the ability to adapt and implement new ideas to cater for the ever-changing needs of the market.




Height - Door and Sidelights

Standard 2100mm

- Optional: Fly screen head and sill option
- Optional: Double high rise interlock
- Optional: Mortise lock with handle

0 = fixed X = sliding

Width



OX



OXX



OXXO



OXXXXO

Both width and height of the unit is 10mm smaller than sizes shown

1500	OX
1800	OX
2000	OX
2100	OX
2400	OX
2700	OX
3000	OX
2210	OXX
2660	OXX
2960	OXX
3110	OXX
3560	OXX
4010	OXX
4460	OXX
3000	OXXO
3600	OXXO
4000	OXXO
4200	OXXO
4800	OXXO
5400	OXXO
6000	OXXO
4420	OXXXXO
5320	OXXXXO
5920	OXXXXO
6220	OXXXXO
7120	OXXXXO

SIDELIGHTS (Also compatible with the ORI-FOLD® Sliding Folding Doors.)

Both width and height of the unit is 10mm smaller than sizes shown



Width
300
600
900



Mortise lock option

Standard Finishes in all regions are Bronze Powder Coated, White Powder Coated and Natural Anodised. Special colours are available.

Palace Sliding Door



Can accommodate Laminated Safety Glass, Toughened Safety Glass and Double Glazing Options. SIG double glazed units are TSG clear combinations.

Available in Double Glazing Sealed Insulated Safety Glass and Double Glazing Sealed Insulated Safety Glass with Low-E on one side for Energy Efficiency.

Height 2100mm and 2400mm

Width


O = fixed X = sliding



OX



OXX



OXXO

Both width and height of the unit is 10mm smaller than sizes shown

1500	OX
1800	OX
2000	OX
2100	OX
2400	OX
2700	OX
3000	OX
3000	OXX
3600	OXX
4200	OXX
4800	OXX
5400	OXX
6000	OXX
3000	OXXO
3600	OXXO
4000	OXXO
4200	OXXO
4800	OXXO
5400	OXXO
6000	OXXO


Origin Hinge Door



SIG double glazed units are TSG clear combinations.

Available in Double Glazing Sealed Insulated Safety Glass and Double Glazing Sealed Insulated Safety Glass with Low-E on one side for Energy Efficiency.

LARGE PANE DOOR




Both width and height of the unit is 10mm smaller than sizes shown

Width

Single Door 900

Double Door 1800

HINGE DOOR WITH MIDRAIL



Both width and height of the unit is 10mm smaller than sizes shown

Width

Single Door 900

Double Door 1800

Height 2100mm



Door Height

1800mm - 2100mm
2101mm - 2400mm
2401mm - 2700mm

Width

Up to 1.8m
1.8m - 2.1m
2.1m - 2.4m
2.4m - 2.7m




3 Panel



3 + 1 Panel

1.8m - 2.1m
2.1m - 2.4m
2.4m - 2.7m
2.7m - 3.0m
3.0m - 3.3m
3.3m - 3.6m
3.6m - 3.9m



3 + 3 Panel

3.0m - 3.3m
3.3m - 3.6m
3.6m - 3.9m
3.9m - 4.2m
4.2m - 4.5m
4.5m - 4.8m
4.8m - 5.1m
5.1m - 5.4m
5.4m - 5.7m



5 Panel

2.4m - 2.7m
2.7m - 3.0m
3.0m - 3.3m
3.3m - 3.6m
3.6m - 3.9m
3.9m - 4.2m
4.2m - 4.5m
4.5m - 4.8m

ORIFOLD® Sliding Folding Doors can accommodate Laminated Safety Glass and Toughened Safety Glass.

Width

3.0m - 3.3m
3.3m - 3.6m
3.6m - 3.9m
3.9m - 4.2m
4.2m - 4.5m
4.5m - 4.8m
4.8m - 5.1m
5.1m - 5.4m
5.4m - 5.7m



5 + 1 Panel




5 + 3 Panel

3.9m - 4.2m
4.2m - 4.5m
4.5m - 4.8m
4.8m - 5.1m
5.1m - 5.4m
5.4m - 5.7m
5.7m - 6.0m
6.0m - 6.3m
6.3m - 6.6m




5 + 5 Panel

5.1m - 5.4m
5.4m - 5.7m
5.7m - 6.0m
6.0m - 6.3m
6.3m - 6.6m




7 Panel

3.3m - 3.6m
3.6m - 3.9m
3.9m - 4.2m
4.2m - 4.5m
4.5m - 4.8m
4.8m - 5.1m
5.1m - 5.4m
5.4m - 5.7m
5.7m - 6.0m
6.0m - 6.3m
6.3m - 6.6m




7 + 1 Panel

3.9m - 4.2m
4.2m - 4.5m
4.5m - 4.8m
4.8m - 5.1m
5.1m - 5.4m
5.4m - 5.7m
5.7m - 6.0m
6.0m - 6.3m
6.3m - 6.6m




7 + 3 Panel

5.1m - 5.4m
5.4m - 5.7m
5.7m - 6.0m
6.0m - 6.3m
6.3m - 6.6m



SILL DETAILS: Origin FlatTrack used for level floor option.



OriGuard®

Retractable Gate



SIDE LOCKING - STANDARD SIZES:

Width	Adjustment	Standard 2080(h) - 2090(h)
900	(700 - 1010)	
1800	(1500 - 1920)	
2400	(1920 - 2460)	

Custom sizes and centre locking option available on request.


STANDARD COLOURS:

White and Bronze

LOCKING OPTIONS:

Side Locking

Centre Locking



Features (Single and Double-sliding):

- Manufactured from a high strength structural grade Aluminium alloy
- Light economical Aluminium design
- Corrosion resistant
- Smooth and silent sliding action
- Instant locking on closure
- Reliable and robust components
- Sliding and fixed options available
- Low maintenance
- Quick and simple DIY installation

*All transactions are subject to Origin Aluminium's standard terms and conditions which are available on request.
Products manufactured in accordance with National Building Regulations.*



Both Origin 340[®] and Origin 38[®] Top Hung Casement windows are available with energy efficient option.

Can accommodate up to 20mm double glazing units for better energy saving and noise reduction.

A1 Denotes deflection design up to 1000 Pa
 A2 Denotes deflection design up to 1500 Pa
 A3 Denotes deflection design up to 2000 Pa

Double Glazing Option A -
 Double Glazing Sealed Insulated Safety Glass

Double Glazing Low-E -
 Double Glazing Sealed Insulated Safety Glass with Low-E on one side for Energy Efficiency.

Origin 340[®] Energy Efficient and Origin 38[®] Energy Efficient Casement Windows have two options of double glazing, for better energy saving and noise reduction.



Both width and height of the unit is 10mm smaller than sizes shown


Standard Finishes in all regions are Bronze Powder Coated, White Powder Coated and Natural Anodised. Special colours are available.

Origin 340[®] and Origin 38[®] Top Hung Casement Window - with energy efficient option



Can accommodate up to 20mm double glazing units for better energy saving and noise reduction. 34mm Outer frame.

Both width and height of the unit is 10mm smaller than sizes shown



Standard Finishes in all regions are Bronze Powder Coated, White Powder Coated and Natural Anodised. Special colours are available.



Domestic Sliding Window (from 600Pa to 1000Pa)

Product Code: PRODUCT CODE PREFIX HS, eg. HS66 etc.



Knysna Sliding Window (up to 2000Pa - can accommodate double glazing units)

Product Code: PRODUCT CODE PREFIX KS, eg. KS66 etc.



Both width and height of the unit is 10mm smaller than sizes shown




Standard Finishes in all regions are Bronze Powder Coated, White Powder Coated and Natural Anodised. Special colours are available.



TRI DOOR


ALL SHOWER HEIGHTS: 1800(h)



Width	Adjustment
700	(676 - 731)
750	(726 - 781)
800	(776 - 831)
850	(826 - 881)
900	(876 - 931)
950	(926 - 981)
1000	(976 - 1031)
1050	(1026 - 1081)
1100	(1076 - 1131)
1150	(1126 - 1181)
1200	(1176 - 1231)




PIVOT DOOR



Width	Adjustment
600	(576 - 631)
650	(626 - 681)
700	(676 - 731)
750	(726 - 781)
800	(776 - 831)
850	(826 - 881)
900	(876 - 931)
950	(926 - 981)
1000	(976 - 1031)



CORNER ENTRY



Width	Adjustment
800	(786 - 814)
900	(886 - 914)
1000	(986 - 1014)
1100	(1086 - 1114)




BI SLIDER

ALL SHOWER HEIGHTS: 1800(h)



Width	Adjustment
1100	(1076 - 1131)
1200	(1176 - 1231)
1300	(1276 - 1331)
1400	(1376 - 1431)


RETURN PANEL



Can be coupled to Pivot Door, Tri Door or Bi-Slider.

Width	Adjustment
600	(576 - 608)
650	(626 - 658)
700	(676 - 708)
750	(726 - 758)
800	(776 - 808)
850	(826 - 858)
900	(876 - 908)
950	(926 - 958)
1000	(976 - 1008)


IN LINE PANEL



Excludes Pivot Door.

Width	Adjustment
300	(284 - 316)
400	(384 - 416)
500	(484 - 516)
600	(584 - 616)

PENTA RETURN PANELS



Excludes Pivot Door - any may be used (Standard is 700mm).

Width	Adjustment
400	(384 - 416) (Sold in sets of 2)
420	(404 - 436) (Sold in sets of 2)

EXTENSION PROFILE



1800(h) 25mm
Extension Profile

FRAMELESS SHOWER

Frameless showers are available on request.

Durban

11 Imvubupark Close
Riverhorse Valley
Durban
Tel (031) 569 6071
Fax (031) 569 6076
dbn@origingroup.co.za

Johannesburg

19 Makriel Road
Wadeville
Germiston
Tel (011) 827 3211
Fax (011) 827 3212
jhb@origingroup.co.za

Cape Town

Unit 2 12-18 Elliot Avenue
Epping 2
Cape Town
Tel (021) 534 6300
Fax (021) 534 6340
ct@origingroup.co.za

Bloemfontein

25 Phillip Fourie Street
East End
Bloemfontein
Tel (051) 432 9107
Fax (051) 432 9106
bloem@origingroup.co.za

Port Elizabeth

Unit 11e 20 Bennett Street
Neave Industrial
Port Elizabeth
Tel (041) 451 1702
Fax (041) 451 1709
pe@origingroup.co.za

Pretoria

301 Battery Street
Silverton
Pretoria 0184
Tel (012) 140 0110
Fax (012) 803 1328
pta@origingroup.co.za

www.origingroup.co.za

